

Enhanced Power Supply Kit - Senior Technician

● 76-300



FEATURES:

- High Quality Retractable Sheath Leads
- Large Spade Lug Adapters
- Silicone Jacketed Lead Wires
- Black & Red Component Colors
- Extra Large Alligator Clips
- Sense Leads
- Storage Pouch

ENHANCED INTERCONNECTION KIT FOR TESTING WITH POWER SUPPLIES:

Tenma's enhanced power supply accessory kit, model 76-300, provides users the necessary connection leads and adapters to begin using the instrument effectively.

The kit includes 1 black and red pair of 1-meter 4mm Stacking Banana Plug leads with retractable safety sheaths, 2 pairs of 4/6 mm Spade Lugs, and 1 pair of Alligator Clips with 4 mm jacks, 1 pair of Extra Large Insulated Alligator Clips, and 1 pair of 1-meter Sense Leads, appropriate accessories for power supply work in education, design, or performance verification.

The lead jackets are silicone for flexibility and burn resistance. The retractable sleeve banana plugs will fit both standard banana jacks and binding posts.

Model 76-300, Power Supply Kit is suitable for instruments from Agilent®, B&K Precision®, Xantrex®, and many others. Find this and other instrument accessories at our web site www.mcmelectronics.com.

APPLICATIONS:

- R&D Laboratories
- Production Test Stations
- Service & Repair Facilities
- Educational Test Benches

ORDER INFORMATION:

76-300

Enhanced Power Supply Kit – Senior Technician

CONTACT INFO:

Sales: 1-800-543-4330

Customer Service: 1-877-626-3532

KIT CONTENTS:

Item	Description	Model	Qty.	Voltage (IEC Rating)	Current Max.
1.	Supply Lead, 100cm (40"), Black	76-500	1	600 V CAT II	12 A
1.	Supply Lead, 100cm (40"), Red	76-502	1	600 V CAT II	12 A
2.	6/4mm Spade Lug Adapter, Black	76-079	2	33Vdc/70Vac	36 A
2.	6/4mm Spade Lug Adapter, Red	76-078	2	33Vdc/70Vac	36 A
3.	Medium Alligator Clips, Black	76-666	1	33Vdc/70Vac	10 A
3.	Medium Alligator Clips, Red	76-668	1	33Vdc/70Vac	10 A
4.	Insulated Alligator Clip, Black	76-572	1	600 V CAT IV	36 A
4.	Insulated Alligator Clip, Red	76-574	1	600 V CAT IV	36 A
5.	Sense Lead Pair, 100cm (40") B/R	76-614	1	33Vdc/70Vac	3 A

SPECIFICATIONS:

- Voltage - (see table)
- Current - (see table)
- Working temperature - -20° to +80° C
- Materials:
 - Body - Brass, Nickel Plated
 - Plastic - Nylon
 - Contacts - BeCu, Nickel Plated

Copyright © 2009, Tenma Test Equipment.
All rights reserved. Information in this publication
supersedes that in all previously published
material. Trade names referenced are the
service marks, trademarks or registered trade-
marks of their respective companies.

Specifications and appearance subject to change without notice
022409

2 - www.tenma.com